



Bondall PTY LTD
ACN: 002 734 096
ARS: 27 002 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

WAPOL FW5 FUNGICIDAL WASH

REVISED: JUNE 2006

DESCRIPTION

Bondall Wapol FW5 Fungicidal Wash is a highly effective bacterial, fungal and algal wash specifically formulated to remove moss, mould and lichen growth off roofs and other surfaces.

On masonry surfaces and concrete tiles the removal of these contaminants is necessary to avoid adhesion problems. Fungal and algal contamination on roofs and other exterior surfaces must be completely killed and removed before the application of any decorative or protective coating.

TEST AREA. Always test on a small inconspicuous area, to ensure that the product is achieving the desired result, prior to application over the entire area.

SURFACE PREPARATION

- Surface preparation is critical and must be strictly observed.
- If the roof is used for the collection of rainwater disconnect the pipe to the storage unit before preparation begins and leave disconnected until after the first substantial rainfall following the application of the Bondall roof coating products.
- Replace any cracked or broken tiles, re-bed the ridge caps where necessary and re-point the ridge caps with Bondall Ridge Pointing Compound.

APPLICATION

- Bondall Wapol FW5 Fungicidal Wash can be applied by brush, swab or gentle spray.
- Apply Bondall Wapol FW5 Fungicidal Wash undiluted to the entire surface to be treated not just to visible areas as some spores may be present in areas which appear to be unaffected. To ensure complete kill and effectiveness, this treatment should be allowed to remain on the surface for at least 24 hours.
- High pressure water clean the roof working from the ridge down to remove all contaminants.
- The surface should then be treated with another application of Bondall Wapol FW5 1:2 water. This application should be allowed to dry completely before commencement of any painting to ensure that any remaining spores on the surface are also killed.

COVERAGE

Bondall Wapol FW5 can be applied at a rate of 7-10m² per litre to concrete cement tiles. This is a guideline only and may vary considerably depending on the type of roof, porosity of the substrate and application technique.

THINNING

Use undiluted for first application. Dilute 1:2 water for second or subsequent applications.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

GLOSS LEVEL

Not applicable.

DRYING TIME

Drying times will vary according to weather conditions at time of application. This treatment should be allowed to remain on the surface for at least 24 hours.

CLEAN UP

Clean all equipment promptly in warm water with a little detergent followed by a fresh water rinse. Do not dispose of into open waterways or drains. Dispose of as per your local council regulations.

COLOUR

Clear liquid.

SIZES

20 litres

PRECAUTION/FIRST AID

- It is recommended that normal protective clothing should be worn, including coveralls, impervious gloves and goggles.
- Avoid unnecessary skin contact and inhalation—use a suitable respirator if spray application is employed.
- If swallowed give a glass of water to drink and contact the Poisons Information Centre on 13 11 26.

Refer to the MSDS for more details.

This data sheet supersedes all previous printed material.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com


DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Advisory Service on 1800 810 123 or (08) 9277 6844 or visit www.bondall.com



Wholly Australian Owned & Manufactured

the solution  bondall

