



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

BONDALL BONDCRETE SBP

REVISED: JAN 2002

DESCRIPTION

Bondall Bondcrete SBP is a very versatile sealing, binding and priming agent for interior and sheltered exterior use. It is a water-based product designed to seal and bind porous, powdery surfaces while it also primes the surface prior to applying water borne decorative paints.

Bondall Bondcrete SBP can be applied to brickwork, stonework, decorative render and concrete floors to prevent oil, dust and stain penetration. Ideal for use on surface prior to carpeting.

TEST AREA

Always test on a small inconspicuous area, to ensure that the product is achieving your desired result, prior to application over the entire area

FEATURES AND BENEFITS

- Easy to use
- Multi-purpose
- Water-based
- Durable
- Economical
- Environmentally friendly

SURFACE PREPARATION

Scrap off all loose and flaking paint. Remove dirt, grease and powdery surfaces by washing down with sugar soap in warm water. Rinse with clean water and allow the surface to dry thoroughly before applying a coat of Bondall Bondcrete SBP.

Please Note:

- Do not use Bondall Bondcrete SBP in permanently wet or damp areas.
- Do not use in temperatures below 10°C
- Bondall Bondcrete SBP is not recommended on plastic, rubber or plaster glass
- Use only water-based paints over Bondall Bondcrete SBP.

APPLICATION

Stir Well.

Apply 1 to 2 coats of Bondall Bondcrete SBP with broom, brush or roller covering the entire area. A third coat maybe required to very porous or powdery surfaces.

COVERAGE

Approximately 6 to 8 square metres per litre depending on the substrate, porosity, texture and application technique.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

THINNING

Not recommended

GLOSS LEVEL

Not applicable.

DRYING TIME

Apply 2-3 coats and allow 12 hours between coats and allow 24 hours before applying decorative paints.

CLEAN UP

Brushes and equipment wash clean in water. Do not pour contents or washings down drains or sinks. Dispose of washings and containers as per council regulations.

COLOUR

Dries clear

SIZES

1 Litre and 4 Litre

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed.

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The wide variety of surfaces and application procedures makes it impossible for us to assume any responsibility for the results obtained.

For further advice please contact the Bondall Building and Renovating Products Advisory Service on 1800 810 123 or visit our web site www.bondall.com



Wholly Australian Owned & Manufactured

the solution  bondall

