



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 8844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

PAVING PAINT

REVISED: JANUARY 2006

DESCRIPTION

Bondall Paving Paint forms a tough hard film with good abrasion resistance and excellent durability, it is ideal for driveways, paths, timber decking, warehouse and garage floors, boat decks and showrooms. It will resist hot tyre pick up if prepared and applied in accordance with the instructions.

Bondall Paving Paint has been tested to CSIRO standard AS3611.1 & AS 4586.1999.

SURFACE PREPARATION

- It is important to prepare the surface correctly before application. The surface to be painted must be thoroughly cleaned and free from dirt, oil, grease etc. Fill holes with a suitable filler and sand lightly to an even finish.
- Some concrete flooring surfaces may suffer from 'renewable moisture' or 'rising damp' and we suggest you test for this prior to painting. Place a piece of clear plastic film (300mm x 300mm) onto the surface and tape all edges down with masking tape. If moisture appears on the inside of the plastic (between 30 min and 2 hours) then renewable moisture is present then the surface should be coated with Bondall Epoxy Prep Surface Conditioner prior to the application of the Paving Paint.

Concrete Surfaces - New

- Allow 6 weeks for newly laid concrete to cure before painting.
- All bare concrete surfaces should be acid etched prior to application with a 1:10 hydrochloric acid and water solution. Broom this solution over the surface and allow to stand for 15 minutes (but do not allow it to dry on surface) before thoroughly washing the surface with water. Properly etched concrete should feel like sandpaper so more than one application may be required.
- Allow surface to dry for at least 3 days after treatment before painting.

Concrete Surfaces - Painted

- Remove any loose or flaking paint by wire brushing or sanding. For larger areas clean the surface with high pressure water cleaner.
- Some previously painted surfaces may not provide adequate adhesion. Test on a small inconspicuous area first.

Timber

- For unpainted timber surfaces, sand thoroughly and dust down. Fill nail holes and cracks before painting.

APPLICATION

- Stir paint thoroughly with a broad, flat stirrer prior to use and frequently during use to keep the "Slip-guard" additive in suspension.
- Once surface is clean, etched and completely dry, dilute the first coat with 20% clean mineral turpentine. This will facilitate penetration and promote adhesion. Apply by brush or short nap roller – do not spray.
- If using more than one can for the final coat, check that the colour is correct in all cans and mix all the paint together to ensure colour consistency before starting final coat.
- Allow to dry for at least 6 hours before applying a second undiluted coat of Paving Paint.
- Do not use in temperatures below 10 °C or if rain is likely within 12 hours.



Wholly Australian Owned & Manufactured

the solution **is** bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

COLOUR

Rivergum, Black, Chestnut, Ferric Red, Forrest Green, Sandstone, Silver Grey, Terracotta, White, Deep Base

COVERAGE

First coat diluted 8-10m² per litre. Second undiluted coat 10-14m² per litre. Coverage is depending on surface porosity and the method of application. This is a guideline only and rates may vary due to these factors.

CLEAN UP

- Clean rim and ensure lid is closed tightly.
- Clean all equipment promptly with mineral turpentine and then rinse thoroughly with fresh water and a little detergent.
- Please dispose of any waste materials responsibly and do not pour excess product down drains or sinks.
- Keep unused product in a sealed container and dispose of according to local council regulations.

PRECAUTION/FIRST AID

- Wear protective clothing (e.g. coveralls, impervious gloves, goggles).
- Avoid contact with eyes and skin.
- Avoid inhalation and ensure good ventilation during use.
- Seal container when not in use.
- Keep out of reach of children.
- If accidental poisoning occurs, seek urgent medical advice or contact the Poison Information Centre on 13 11 26.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

