



Bondall PTY LTD  
ACN: 008 734 996  
ABN: 27 008 734 996

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4068

bondall@bondall.com  
www.bondall.com

## WAPOL ROOF PRIMER

REVISED: JUNE 2006

### DESCRIPTION

WAPOL ROOF PRIMER is based on a styrene acrylic emulsion. It is designed to promote inter-coat adhesion between the substrate and the top-coat when used on metal roofs or terra cotta tiles or between the sealer if used on concrete tiles.

WAPOL ROOF PRIMER is suitable for use on sealed concrete tiles, terra cotta tiles and some pre-coated metal roofs (please test if unsure).

### SURFACE PREPARATION

- Surface preparation is critical and must be strictly observed. The type and amount of surface preparation will vary with the type of roof so please observe our surface preparation guidelines mentioned in the Bondall CFA Roof Coat data sheet.
- Surfaces must be free from grease, grime, dust, dirt, moss, lichen, loose and flaking paint and surface oxidation.
- If the roof is used for the collection of rainwater disconnect the pipe to the storage unit before preparation begins and leave disconnected until after the first substantial rainfall following the application of the CFA Roof Coat system.
- Replace any cracked or broken tiles and/or secure metal sheets and check for rust patches (wire brush and treat with a rust converter following the manufacturer's directions).
- Clean the roof with a high-pressure water cleaner working from the ridge down to remove all moss, lichen or other contaminants.
- For concrete and terra cotta tiled roofs re-bed the ridge caps where necessary and re-point the ridge caps with Bondall Ridge Pointing Compound.
- If moss or mould is still present it should be treated with Wapol FW5 Fungicide Wash. (Refer to FW5 data sheet for procedure)

### APPLICATION

- Apply by airless spray using a spray tip between 0.19-0.26. Product can also be applied by brush or roller if required.

### COVERAGE

Wapol Roof Primer will cover approximately 7 square metres per litre depending on the type of roof, porosity of the substrate, and application technique. When used as a misting coat spreading rate should be between 12-15 square metres per litre.

### THINNING

Not normally required but may be thinned with approximately 5% water to assist with application in warm weather.

### GLOSS LEVEL

Matt finish



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD  
ACN: 008 734 996  
ABN: 27 008 734 996

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4068

bondall@bondall.com  
www.bondall.com

## DRYING TIME

Wapol Roof Primer is touch dry in approximately 30 minutes and can be re-coated after 4 hours. Drying times are a guide only and longer drying times may be required under humid or cool conditions. Do not apply Wapol Roof Primer if the temperature is below 10°C or above 35°C or if rain is expected within 24 hours.

## CLEAN UP

Clean all equipment promptly with warm water with a little detergent followed by a fresh water rinse. Do not dispose of into open waterways or drains. Dispose of as per your local council regulations.

## COLOUR

Light Grey

## SIZES

1 Litre and 4 Litre

## PRECAUTION/FIRST AID

- It is recommended that normal protective clothing should be worn, including coveralls, impervious gloves and goggles.
- Avoid unnecessary skin contact and inhalation—use a suitable respirator if spray application is employed.
- If swallowed give a glass of water to drink and contact the Poisons Information Centre on 13 11 26.

Refer to MSDS for more details.

This data sheet supersedes all previous printed material.

## DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall



Quality  
Endorsed  
Company  
ISO 9002 L: 2108  
Sydney Australia