



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

WAPOL ROOF SEALER-CLEAR

REVISED: JUNE 2006

DESCRIPTION

Bondall Wapol Roof Sealer is formulated from a specially selected waterborne resin. It provides excellent penetration into weathered concrete/cement or other uncoated cementitious surfaces. Bondall Wapol Roof Sealer will reduce the porosity of the surface and provide a suitable surface for the application of Bondall CFA Roof Coat.

SURFACE PREPARATION

- Surface preparation is critical and must be strictly observed. Surfaces must be free from grease, grime, dirt, moss, lichen, loose and flaking paint and surface oxidation.
- If the roof is used for the collection of rainwater disconnect the pipe to the storage unit before preparation begins and leave disconnected until after the first substantial rainfall following the application of the CFA Roof Coat system.
- Clean the entire roof with a high-pressure water cleaner working from the ridge down to remove all moss, lichens or other contaminants.
- Re-bed the ridge caps where necessary and re-point the ridge caps with Bondall Ridge Pointing Compound.

APPLICATION

- Stir Bondall Wapol Roof Sealer thoroughly prior to use.
- Apply one coat of Bondall Wapol Roof Sealer by brush, roller or airless spray to a slightly damp surface and ensure all tiles are evenly covered.
- Allow Bondall Wapol Roof Sealer to dry for a minimum of 4 hours before application of CFA Roof Coat.

COVERAGE

Bondall Wapol Roof Sealer will cover approximately 5–10 square metres per litre depending on the type of roof, the porosity of the substrate, tip sizes and application technique.

DRYING TIME

Wapol Roof Sealer is touch dry in approximately 30 minutes and can be re-coated after 2 hours. Drying times are a guide only and longer drying times may be required under cool or humid conditions. Do not apply Wapol Roof Sealer if the temperature is below 10°C or if rain is expected within 24 hours.

CLEAN UP

Clean all equipment promptly with warm water with a little detergent followed by a fresh water rinse. Do not dispose of into open waterways or drains. Dispose of as per local council regulations.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

SIZES

20 Litres

PRECAUTION/FIRST AID

- It is recommended that normal protective clothing should be worn, including coveralls, impervious gloves and goggles.
- Avoid unnecessary skin contact and inhalation—use a suitable respirator if spray application is employed.
- If swallowed give a glass of water to drink and contact the Poisons Information Centre on 13 11 26.

Refer to the MSDS for more details.

This data sheet supersedes all previous printed material.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Advisory Service on 1800 810 123 or (08) 9277 6844 or visit www.bondall.com



Wholly Australian Owned & Manufactured

the solution  bondall

